



Keep Forsyth Beautiful Recycling Trailer Terms & Conditions of Transporting Trailer



Renter shall name Forsyth County Board of Commissioners as Additional Insured to their Automobile and Liability Insurance Policy as respects to the Keep Forsyth County Beautiful Recycling Trailer for the dates and times that the trailer will be in the possession of the Renter and a Certificate of Insurance must be provided to Forsyth County Risk Management, C/O Charity Clark, Risk Manager, 100 East Main Street, Suite 230, Cumming GA 30040 prior to transport of trailer.

1. Tow vehicles and trailers must have compatible hitching, braking, and wiring systems to ensure safety. Please review important towing concerns below:
2. Be sure your hitch is rated for 3, 5000 lbs. The hitch ball should be a 2" ball. The ball height should be 18" from top of ball to the ground for optimum towing safety.
3. For trailer brakes to operate, a brake controller must be installed in the tow vehicle.
4. Trailer requires a round 7-way electrical plug for lights and brakes to have power. Lights should be checked before towing, including blinders, running lights and brake lights. Lights, including interior lights operate only when tow vehicle running lights are on.
5. Break away system is installed to stop trailer should it become detached from towing vehicle during transit. Break away line must be secured to tow vehicle hitch, so that if separated, the brakes shall be activated. Electric brakes will not work in conjunction with tow vehicle unless tow vehicle has a brake controller box installed.
6. A lock or pin should be placed in the coupler latch to ensure safe towing. Coupler latch should be in the down or flat position and then secured with lock or pin.
7. All doors and ramps should be closed and locked prior towing. Vent should be in the closed position for towing.
8. Do not walk on roof, it is not meant to support your weight.
9. Keep roof vents closed in transit.

10. Safety chains should be crossed when hooking up your trailer. Chains that are too long may be twisted to shorten them for towing. Remember to leave some slack for turning; however, do not let them drag the ground. After loading your trailer, recheck the chains prior to towing. A ground wire is needed from the plug to the frame of your tow vehicle. The safety chains are not an adequate ground.

11. Most flat tires are felt immediately, as the towing vehicle starts to pull, sway, or shake. Immediately pull your vehicle over to a safe location off of the roadway to change the tire.

In case of an accident, theft, damage to the trailer or damage to any trailer contents contact Keep Forsyth County Beautiful immediately at 770 205-4573 or 678 294-9753.

REPRESENTATIVE SIGNATURE

DATE

KEEP FORSYTH BEAUTIFUL EMPLOYEE

DATE